

# CERTIFICATE OF COMPLIANCE

**Certificate Number** 20160107-R38253  
**Report Reference** R38253-20151228  
**Issue Date** 2016-JANUARY-07

**Issued to:** Colt International Licensing LTD  
New Lane  
Havant  
P09 2LY UNITED KINGDOM

**This is to certify that representative samples of** FIRE-PROTECTIVE CURTAINS  
See Addendum.

Have been investigated by UL in accordance with the Standard(s) indicated on this Certificate.

**Standard(s) for Safety:** UL 10D, Fire Tests of Fire Protective Curtain Assemblies.  
UL 1784, Air Leakage Tests of Door Assemblies and Other Opening Protectives.

**Additional Information:** See the UL Online Certifications Directory at [www.ul.com/database](http://www.ul.com/database) for additional information

Only those products bearing the UL Certification Mark should be considered as being covered by UL's Certification and Follow-Up Service.

Look for the UL Certification Mark on the product.



Bruce Mahrenholz, Director North American Certification Program  
UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>



# CERTIFICATE OF COMPLIANCE

Certificate Number 20160107-R38253  
Report Reference R38253-20151228  
Issue Date 2016-JANUARY-07

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

Single-barrel fire-protective curtains, FA1 Series, SA1 Series and SD1 Series, surface or between jamb mounted, maximum 3620 mm (142 in.) wide by 3025 mm (119 in.) high. Maximum wall opening area of 10.95 m<sup>2</sup> (117 ft<sup>2</sup>). When greater than 3620 mm (142 in.) wide by 3025 mm (119 in.) high, the single-barrel assembly is eligible for the Oversize Label and may be produced up to 6000 mm (236.2 in.) wide by 12000 mm (472.4 in.) high.

Multi-barrel fire-protective curtains, FA1 Series and SA1 Series, surface or between jamb mounted, maximum 3620 mm (142 in.) wide by 3025 mm (119 in.) high. Maximum wall opening area of 10.95 m<sup>2</sup> (117 ft<sup>2</sup>). When greater than 3620 mm (142 in.) wide by 3025 mm (119 in.) high, the single-barrel assembly is eligible for the Oversize Label and may be produced up to 6000 mm (236.2 in.) wide by 12000 mm (472.4 in.) high.

#### MODEL DESIGNATION:

Fire-protective curtain, Model FA1.  
Model FA1/60, 1 hr fire rating  
Model FA1/180, 3 hr fire rating  
Fire-protective curtain, Model SA1.  
Model SA1/60, 1 hr fire rating  
Model SA1/180, 3 hr fire rating

The products below have been additionally investigated to ANSI/UL 1784

Fire-protective curtain, Model FA1.  
Model FA1/S1/60, 1 hr fire rating  
Model FA1/S1/180, 3 hr fire rating  
Fire-protective curtain, Model SA1.  
Model SA1/S1/60, 1 hr fire rating  
Model SA1/S1/180, 3 hr fire rating  
Fire-protective curtain, Model SD1.  
Model SD1/60, 1 hr fire rating  
Model SD1/180, 3 hr fire rating



Bruce Mahrenholz, Director North American Certification Program

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/about/locations/>

